

Biobarrier® : Retaining Wall Application

**TYPAR Geosynthetics** Toll-Free: 1-800-541-5519 e.mail: geo.sales@pginw.com website: www.typargeosynthetics.com 70 Old Hickory Blvd. Old Hickory,

NOT FOR CONSTRUCTION Copyright © Polymer Group Inc. All rights reserved Typar<sup>®</sup> is a registered trademark of Polymer Group Inc.

DISCLAMMER.
THE INFORMATION CONTAINED IN THIS DETAIL IS PROVIDED FOR THE CONVENIENCE OF THE USER AND DOES NOT TAKE PLACE OF CONSTRUCTION PLANS AND/OR SPECIFICATIONS, PCYVARE RODUL, INC. CAMPIOTE BELD TAKE PLACE OF CONSTRUCTION PLANS AND/OR SPECIFICATIONS, PCYVARE RODUL, INC. CAMPIOTE BE USE OR MISSINGS OF THIS INFORMATION, WE RECOMMEDITED ON CONTINUE OF FOR PRITHER DESIGNA ASSISTANCE EL USE OR MISSISTANCE. THIS DETAIL IS FOR CONCEPT PURPOSES ONLY AND DOES NOT IMPLY ANY ACTUAL DESIGN OR ENGINEERING HAS BEEN COMPLETED. ENGINEERING NOUS LINE WILL HELD THE SPECIFICATION OF PURPOSE ONLY AND DOES NOT IMPLY ANY ACTUAL DESIGN OR ENGINEERING HAS BEEN COMPLETED. ENGINEERING NOUS LINE WILL HELD THE SPECIFICATION INCLUDING SAND AND AND AGREGATE.
ALL MATERIALS ARE SUBJECT TO APPROVED BY POLYMER GROUP INC.

Note 1: Contact your utility company prior to trenching. Consult a professional arborist if root trimming is required.

Note 2: Install & Cover Biobarrier® as soon as possible (within 12 hours) after opening. High temperatures and direct sunlight can reduce

Note 2: Initial 8. Cover biocharmer\* as soon as possable (within 12 hours) after opening. High temperatures and direct suringly can reduce effective product file.

effecti

Specific advice on the use of Biobarrier® can be obtained from Polymer Group Inc.

Table 1 : Biobarrier® Specifications

Description	Data			
Product Chemical Family	Biobarrier® Root Control System Thermoplastic Polyotefin			
	Polypropylene	> 74.8%		
Composition	UV Stabilizer	< 5%		
	Trifluralin	< 20%		
	Pigment Masterbatch <sup>1</sup>	< 0.5%		
Appearance Physical State Vapor Pressure* Boiling Point Solubility (H <sub>2</sub> O)* Vapor Density Packing Density Odor pH Solubility (H <sub>2</sub> O)* Specific Gravity Percent Voidifie UV real-stance Corroshty Flamability Toxidity Hygroscopicity Esploshty Esploshty	Gray Fabric Solid 13.7 mPa @ 25°C Not Applicable 0.2 ppm @ 25°C Not Applicable None None			
Fabric				
Unit Welght Tensile Strength (lbs.) Elongation at Break (%) Mullen Burst Strength (psl) Puncture Strength (lbs.) Coefficient of Permeability (cm/sec.)	4.0 45.0 > 70.0 175.0 50.0 3 x 10 <sup>2</sup>			
Nodule	•			
Base Dlameter (In.) Helght Welght (os.) Spacing (In.)	7/16 1/4 0.013 1-1/2			

Chart 1: Examples of Intended Biobarrier® Root Control Applications & Roll Widths

Application	Root Control Width in. (cm)						
	12 (30)	19.5 (50)	24 (61)	29 (74)	39 (99)	58.5 (14	
Building Foundations					X	X	
Burial Vaults/Tombstones						Х	
Containers			X	Х	X	X	
Curbs		X	Х				
Drain Lines	X	X	X	X	X	X	
Earthdams						X	
Golf Greens/Tees/Cart Paths		Х	X	X	X		
Landfills						X	
Medians			X	X	Х		
Paths	X	X	Х	Х			
Planting Beds		X	X	X	X	X	
Pot 'N' Pot	SOLD IN 6" X 12" SWATCHES (500/BOX)						
Pots	X	X					
Retaining Walls				X	X	X	
Roads		X	X	X			
Roof Gardens					X	X	
Septic Tanks/Fields						X	
Sidewalks		X	X	X			
Swimming Pools		X	Х	Х	X		
Tennis Courts		X	X	X	X		
Underground Pipes/Cables	X	X	X	X	X	X	
Underground Storage Tanks						X	
		X	X	X	X		

Chart 1 is a general guide only. Your specific applications may require slightly different sizes. As a general rule, the greater the fabric width, the greater the degree of protection against costly root clarrange. But, like any other root barrier the protection does not extend beyond the edge of the fabric. So this important to use adequate length and width to assure proper protection.

This field guide is provided as an aid to assessing root control in commonly encountered site conditions. Polymer Group Inc. accepts no responsibility for any loss or damage resulting from the use of this guide.

Please note that the information above is given as a guide only. All sizes and weights are nominal figures and may vary to what is published. Polymer Group inc. cannot be liable for damage caused by incorrect installation of this product. Final determination of the suitability of any information or material for the use contemplated and the manner of its use is the sole responsibility of the user and the user must assume all risk and responsibility in connection therewith.