

BODPAVE®85

Product Data Sheet

Issue: 02.B8513 Date: 06.25.12 Page: 1 of 1

| | |
|------------------------------------|--|
| Physical Properties | |
| Structure | Rigid-walled, flexible semi-closed cell combination |
| Polymer | 100% recycled polyethylene (HDPE) |
| Color Options | (1) Black, Green and Natural |
| Grid Connection Type | Overlapping edge loop and cell connection |
| Grid Interlock Type | Integral self locking snap-fit clips |
| Dimensional Characteristics | |
| Paver Size | 19.7" x 19.7" |
| Installed Paver Size | 19.7" x 19.7" (4 grids per 1.2 yd ²) |
| Height | 1.97" |
| Ground Spike Length | 1.37" |
| Weight | 3.4lbs/paver |
| Nominal Internal Cell Size | Castellated 2.6" Plaque & 1.8" Round shaped |
| Cell Wall Thickness | 0.1" - 0.2" |
| Open Cell % | Top 92% / Base 75% |
| Technical Characteristics | |
| Load Bearing Capacity (Filled) | < 367 tons/ yd ² |
| Crush Resistance (Unfilled) | (2) < 275 tons |
| Basal Support & Anti Shear | Integral 1.35" long cross & 'T' section ground spikes (18 per paver) |
| Chemical Resistance | Excellent |
| UV Resistance | High |
| Toxicity | Non Toxic |

Notes:

(1) Green and Natural subject to minimum order requirements

(2) Research carried out by Sheffield University UK Department of Mechanical Engineering. (Rennison/Allen March 2009)

As part of its continual improvement process, Fiberweb, Inc. reserves the right to change the properties listed on this data sheet without prior notice.

® indicates a registered trademark of Fiberweb, Inc. or a Fiberweb Group company, many of which are registered in a number of countries around the world.